

Product data sheet

Characteristics

PDLE392C-AG

PDL Iconic, cover frame, 2 switches & 2 sockets, 10 A, vertical, ash grey



Main

| | |
|---------------------------|----------------------------|
| Range | PDL Iconic |
| Aesthetic name | Iconic Essence |
| Product or component type | Cover frame |
| Colour tint | Cover frame: ash grey (AG) |
| Type of packing | Polybag |
| Quantity per set | Set of 10 |

Complementary

| | |
|--------------------------------|---|
| Range compatibility | Switched socket |
| Product destination | Switched socket |
| Device mounting | Flush |
| Number of rocker | 2 |
| Number of power socket outlets | 2 |
| [In] rated current | 10 A |
| Installation direction | Vertical |
| Fixing mode | Clip-on |
| Surface finish | Matt |
| Material | PC (polycarbonate): window ABS (acrylonitrile butadiene-styrene): skin Timber |
| Height | 131.0 mm |
| Width | 85 mm |
| Depth | 8.5 mm |
| Net weight | 0.03 kg |

Environment

| | |
|---------------------------------------|-----------|
| Ambient air temperature for storage | 0...45 °C |
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity | 10...95 % |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.