

### Product data sheet Characteristics

# PDL392USBAC-VW

PDL Iconic, switched socket, 2 switch & 2 socket, USB, vert, 10 A, Vivid White



Main	
Range	PDL Iconic
Product or component type	Switched socket
Device presentation	Complete product
Outlet poles configuration	2P + E with shutter
Outlet standard	Australian

#### Complementary

Device mounting	Flush	
Number of power socket outlets	2	
Number of rocker	2	
Outlet standard description	With earthing contact	
Outlet standard	Australian/New Zealand	
Ground lug position	Straight 180° position	
Device composition	2 USB charger	
Fixing mode	By screw	
Installation direction	Vertical	
Colour	Vivid white (VW)	
Surface finish	Matt	
Type of packing	Polybag	
Quantity per set	Set of 10	
Sale per indivisible quantity	1	
Connections - terminals	3 screw terminals	
Screwdriver shape	Square drive no 1 (SQ1)	
Clamping connection capacity	1 x 2.54 x 2.5 mm² for stranded cable(s)	
Wire stripping length	16 mm	
Material	PC (polycarbonate): skin	
Height	120 mm	
Width	78 mm	
Depth	44 mm	

#### Environment

Ambient air temperature for storage	060 °C
Ambient air temperature for operation	045 °C
Relative humidity	1095 %
Standards	AS/NZS 3112

### Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	135 g	
Package 1 Height	152 mm	
Package 1 width	78 mm	
Package 1 Length	135 mm	

## Offer Sustainability

EU RoHS Directive	Under investigation