

**Product data sheet**  
Characteristics

**PDL600RM**  
Relay Module 600 Series - 240 V - 6 AX



**Main**

Range of product	600 Series
Product or component type	Switch

**Complementary**

Material	PC (polycarbonate)
Colour tint	White
Surface finish	Opaque
Installation direction	Vertical
Width	37 mm
Height	23 mm
Rated current	6 AX 16 A
[Ue] rated operational voltage	230/240 V
Network frequency	50 Hz
Network number of phases	1 phase
Number of poles	1
Mounting mode	Front
Ambient air temperature for operation	-40...70 °C
Contacts type and composition	NO/NC

**Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	44 g
Package 1 Height	30 mm
Package 1 width	40 mm
Package 1 Length	150 mm

**Offer Sustainability**

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

---

China RoHS Regulation

 [China RoHS Declaration](#)

---

Environmental Disclosure

 [Product Environmental Profile](#)

---