


Product data sheet
Characteristics

PDL378M10L
Switch 300 Series Mechanism - Intermediate -
1-or 2-way - 250 V - 10 A



Main

Range of product	PDL Iconic
Product or component type	Switch
Device application	Lighting
Device presentation	Mechanism
Provided equipment	LED Switch
Type of packing	Polybag
Quantity per set	Set of 20
Sale per indivisible quantity	1
Motor M-rating AS3133	M80
Load type	Inductive Light Fluorescent lamp
Light source	LED 60 mW

Complementary

Switch function	1/2-way
Fixing mode	By screws
Rated current	10 AX at 250 V AC 50 Hz
Electrical durability	20000 cycles conforming to AS/NZS 60669
Connections - terminals	4 screw terminals
Screwdriver shape	Square drive no 1 (SQ1) Philips No 2
Clamping connection capacity	1.5 mm ² for stranded cable(s) 1.5 mm ² for flexible cable(s) 1.5 mm ² for rigid cable(s)
Wire stripping length	10 mm
Local signalling	LED warm white optional LED warm white for locator LED warm white for indicator
Material	PC (polycarbonate): housing PA66: housing
Height	23 mm
Width	23 mm
Depth	32 mm
Net weight	0.016 kg

Environment

Dielectric strength	20000 V
Ambient air temperature for operation	0...45 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	10...95 %
Product certifications	RCM

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	23 g
Package 1 Height	23 mm
Package 1 width	23 mm
Package 1 Length	23 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile