

Product data sheet

Characteristics

PDL89DI

Universal Double Insulated Mounting Block; Polycarbonate, White



Main

Range of product	PDL General Accessories
Product or component type	Mounting plate
Colour tint	White
Quantity per set	Set of 8
Type of packing	Carton

Complementary

Material	PC (polycarbonate)
Surface finish	Glossy
Installation direction	Horizontal Vertical
Device mounting	Surface
Width	74 mm
Depth	44 mm
Length	118 mm
Fixing center	84 mm

Environment

Ambient air temperature for operation	-10...40 °C
---------------------------------------	-------------

Packing Units

Package 1 Weight	116.000 g
Package 1 Height	119.000 mm
Package 1 width	75.000 mm
Package 1 Length	45.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.