

## Product data sheet

### Characteristics

# PDL56SO316/240LERW

Socket - Twin, 16A, 250V, 2-Gang, 3- Flat Pin,  
Resistant White



### Main

Range of product	56 Series™
Product brand	PDL
Product or component type	Socket-outlet
Quantity per set	Set of 2
Type of packing	Carton

### Complementary

Material	PC + PET
Colour tint	White
Surface finish	Gloss
Installation direction	Vertical
Width	95 mm
Height	191 mm
Depth	35 mm
Rated current	16 A
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Network number of phases	1 phase
Number of gangs	2 gangs
Pin number	3
Device composition	Round pin
Mounting mode	Surface mounted
Fixing center	84 x 84 mm
Cable cross section	0.75... 10 mm <sup>2</sup>

### Environment

IP degree of protection	IP66
Ambient air temperature for operation	-40...55 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	230.484 g
Package 1 Height	3.5 cm
Package 1 width	9.5 cm
Package 1 Length	19.1 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	4

Package 2 Weight	1.021 kg
Package 2 Height	8.3 cm
Package 2 width	19.2 cm
Package 2 Length	19.2 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	8
Package 3 Weight	2.2 kg
Package 3 Height	20.0 cm
Package 3 width	18.0 cm
Package 3 Length	22.0 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>