

Product data sheet

Characteristics

PDL56E2RW

Enclosure, 2-Gang, 1x25mm 1x32mm Conduit Entry, Resistant White



Main

| | |
|---------------------------|-----------|
| Range | 56 Series |
| Product or component type | Enclosure |

Complementary

| | |
|------------------|--------------------------|
| Mounting mode | Surface mounted |
| Fixing center | 60 x 156 mm |
| Number of gangs | 2 x 1 gang |
| Material | PVC (polyvinyl chloride) |
| Surface finish | Gloss |
| Colour tint | White |
| Length | 198 mm |
| Width | 102 mm |
| Depth | 63 mm |
| Quantity per set | Set of 6 |
| Type of packing | Carton |

Environment

| | |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -40...55 °C |
| IP degree of protection | IP66 |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 452.0 g |
| Package 1 Height | 6.3 cm |
| Package 1 width | 10.2 cm |
| Package 1 Length | 19.8 cm |

Offer Sustainability

| | |
|-------------------|---------------------|
| EU RoHS Directive | Under investigation |
|-------------------|---------------------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.