

Product data sheet

Characteristics

PDL501J/50

PDL Single Screw Connectors 40Amp 500VAC - 3x6mm² or 4x2.5mm² Cables - Jar of 50



Main

Range of product	PDL General Accessories
Product or component type	Connection terminal
Colour tint	Translucent
Quantity per set	Set of 50
Type of packing	Jar

Complementary

Material	Polypropylene
[In] rated current	40 A
Rated voltage	500 V AC 50 Hz
Height	14 mm
Width	25 mm
Depth	23 mm
Connections - terminals	3 x 6 mm ² screw terminals

Environment

Ambient air temperature for operation	-10...40 °C
---------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.2 cm
Package 1 Width	6.5 cm
Package 1 Length	6.5 cm
Package 1 Weight	0.221 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	17.7 cm
Package 2 Width	16.5 cm
Package 2 Length	24.2 cm
Package 2 Weight	2.21 kg

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
-------------------	--

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.