

Product data sheet

Characteristics

CLITPFLT50

LED floodlight, Clipsal - Lighting, 50W, 4000K, IP65, black



Main

Range	Clipsal
Product or component type	Floodlight
Device application	Lighting
Main colour tint	Black
Colour tint	Black

Complementary

Type of installation	Outdoor
Device mounting	Surface Ceiling
Total system power	50 W
Light source	LED
[Ue] rated operational voltage	230 V AC 50 Hz
Luminous flux	0...95 % RH non-condensing: 5250 lm
Colour rendering index	R _a =80
Bulb lifespan	50000 h
Colour temperature	4000 K
Beam angle	110 °
Height	Outdoor: 210 mm
Width	155 mm
Depth	33 mm
Net weight	1.45 kg
Cable length	0.6 m

Environment

Environmental characteristic	Weatherproof
IP degree of protection	IP65
Ambient air temperature for operation	-20...40 °C
Relative humidity	10...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	20.4 cm
Package 1 Length	22 cm
Package 1 Weight	969 g
Unit Type of Package 2	CAR

Number of Units in Package 2	6
Package 2 Height	23 cm
Package 2 Width	25.5 cm
Package 2 Length	33 cm
Package 2 Weight	6.343 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	3-Years
----------	---------