EVH5A11N2C7

Charging station, Schneider Charge, 3P+N, attached cable 7m, 11kW, 16A





Main Range Schneider Charge Product name Schneider Charge Product or component type Charging station Poles description 3P + N Mounting mode Wall-mounted Max power 11 kW 16 A Number of charge point 1

Attached cable T2 bottom 7 m

Complementary

Rated supply voltage	400 V AC 5060 Hz +/- 10 %
Earthing system	IT 230 TT TN-S
Number of inputs	1
Input type	Dry contact for dynamic energy management
Local signalling	Red, green and blue 1 LED, function: status indication
Protection type	Earth-leakage protection
Height	352 mm
Width	244 mm
Depth	117 mm
Net weight	5.1 kg
Colour	White/green
Standards	EN 61851 IEC 61851-1
Communication network type	Wi-Fi Wireless Ethernet
Communication port protocol	OCPP 1.6, for connection to the Schneider Electric Wiser app

Connection to the

vehicle

Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
IK degree of protection	IK10
Ambient air temperature for operation	-3555 °C
Ambient air temperature for storage	-4085 °C
Relative humidity	595 %
Operating altitude	02000 m

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	30.000 cm	
Package 1 Width	29.000 cm	
Package 1 Length	48.000 cm	

Package 1 Weight	7.490 kg	
Unit Type of Package 2	P12	
Number of Units in Package 2	18	
Package 2 Height	103.000 cm	
Package 2 Width	80.000 cm	
Package 2 Length	120.000 cm	
Package 2 Weight	147.000 kg	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€ Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information