

## Product data sheet

### Characteristics

# PDLO381-XW

Switch, PDL Iconic, 20A/16AX, 250 V, 1 Gang, horizontal, Extra White



### Main

Range of product	Iconic
Range of product	PDL Iconic
Product or component type	Switch
Product brand	PDL
Device application	Lighting
Device presentation	Complete product
Colour	White (XW)

### Complementary

Device mounting	Surface
Switch function	1-pole 1/2-way
Number of gangs	1 gang
Number of rocker	1
Actuator	Rocker
Fixing mode	By screws By clipping locks
Surface finish	Matt
Surface treatment	Untreated
Rated current	20 A at 250 V AC 50 Hz 16 AX at 250 V AC 50 Hz
Electrical durability	12000 cycles
Connections - terminals	4 screw terminals
Screwdriver shape	Square drive no 1 (SQ1) Phillips No 2
Clamping connection capacity	4 x 1.5 mm <sup>2</sup> 3 x 2.5 mm <sup>2</sup>
Wire stripping length	10 mm
Local signalling	Without
Material	PC (polycarbonate) TPE (thermoplastic elastomer) ABS (acrylonitrile butadiene-styrene) POM (polyoxymethylene)
Height	85 mm
Width	115.5 mm
Depth	70 mm
Net weight	0.19 kg

### Environment

Ambient air temperature for operation	0...45 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	10...95 %
Standards	AS/NZS 3133
IP degree of protection	IP56

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Halogen content performance	Halogen free plastic parts product