

Product data sheet

Characteristics

PDLO394-BK

Single switched socket, PDL Iconic Outdoor, horizontal, 10A 250V, Black



Main

| | |
|----------------------------|------------------|
| Range | Iconic |
| Product or component type | Switched socket |
| Device presentation | Complete product |
| Product brand | PDL |
| Switch application | On/off switching |
| Outlet poles configuration | 1P + E |
| Outlet standard | Australian |

Complementary

| | |
|--------------------------------|---|
| Socket-outlet type | Single socket-outlet |
| Control type | Rocker |
| Device mounting | Wall mounted |
| Mounting position | Horizontal |
| Number of power socket outlets | 1 |
| Number of rocker | 1 |
| Range compatibility | Iconic |
| Outlet standard description | With earthing contact |
| Outlet standard | Australian/New Zealand |
| Pin number | 3 |
| Fixing mode | By screw |
| Installation direction | Horizontal |
| Colour | Black (BK) |
| Surface finish | Matt |
| Type of packing | Box |
| Sale per indivisible quantity | 1 |
| Rated current | 10 A at 250 V AC 50 Hz |
| Electrical durability | 12000 cycles |
| Connections - terminals | 3 screw terminals |
| Screwdriver shape | Square drive no 1 (SQ1) Phillips No 2 |
| Clamping connection capacity | 3 x 2.5 mm ² 2 x 4 mm ² |
| Wire stripping length | 16 mm |
| Material | PC (polycarbonate) ABS (acrylonitrile butadiene-styrene) POM (polyoxymethylene) |
| Type of installation | Outdoor |
| Height | 85 mm |
| Width | 115.5 mm |
| Depth | 70 mm |
| Net weight | 0.22 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|-------------|
| Ambient air temperature for storage | 0...60 °C |
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity | 10...95 % |
| Standards | AS/NZS 3112 |
| Product certifications | RCM |
| IP degree of protection | IP54 |

Offer Sustainability

| | |
|-----------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Halogen content performance | Halogen free plastic parts product |